



76-B4442



CE

ASTM

4

( 76-B444X ) 6  
76-B446X

4

( 76-B446X )  
6 4



128×80

6

CE



ASTM D1559 ASTM D5581 AASHTO T245 ASTM D6926



|       |   |   |
|-------|---|---|
|       | <b>76-B4442</b><br><b>76-B4443</b><br><b>76-B4444</b> | <b>76-B4462</b><br><b>76-B4463</b><br><b>76-B4464</b> |
|       | 800W  | 2000W   |
| ( / ) | 55±5  | 55±5  |
|       | 98.5mm  | 149.4mm   |
|       | 4536±9g   | 10.21±0.01kg  |
|       | 457±3mm   | 457±2mm   |
|       | 385×470×1867mm  | 423×578×1861mm  |
|       | 150kg   | 170kg   |



76-B4442



76-B4442



76-B4000/CB ASTM EN



**76-B4442**

T245 4 ASTM D1559, D6926 AASHO  
230V 50Hz 1 ph

**76-B4443**

T245 4 ASTM D1559, D6926 AASHO  
220V 60Hz 1 ph

**76-B4444**

T245 4 ASTM D1559, D6926 AASHO  
110V 60Hz 1 ph

**76-B4462**

6 4 ASTM D5581  
6 4  
230V 50Hz 1 ph

**76-B4463**

6 4 ASTM D5581  
6 4  
220V 60Hz 1 ph

**76-B4464**

6 4 ASTM D5581  
6 4  
110V 60Hz 1 ph



**33-T3712/CB**

CBR-Proctor 33-T371X 76-B444X  
B443X B446X

**76-B4460/1**

6 4 76- B446X 4